UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED OMB No. 1004-0136 Expires July 31, 2010

BUREAU OF LAND N	5. Lease Serial No. UTU472		
APPLICATION FOR PERMIT	TO DRILL OR REENTER	6. If Indian, Allottee or Tribe	Name
la. Type of Work: 🛛 DRILL 🔲 REENTER		7. If Unit or CA Agreement, I NATURAL BUTTES U	
1b. Type of Well: ☐ Oil Well ☐ Gas Well ☐ Oth	ner 🗖 Single Zone 🔀 Multiple Zone	Lease Name and Well No. NATURAL BUTTES UNI	IT 649-26E
	KAYLENE R GARDNER gardner@eogresources.com	9. API Well No. 43-84-	7-34870
3a. Address 1060 EAST HIGHWAY 40 VERNAL, UT 84078	3b. Phone No. (include area code) Ph: 435-781-9111	10. Field and Pool, or Explora NATURAL BUTTES/V	
4. Location of Well (Report location clearly and in accordance) At surface NWNE 661FNL 1759FEL 3		11. Sec., T., R., M., or Blk. ar Sec 26 T10S R22E M	•
At proposed prod. zone NWNE 661FNL 1759FEL 3	9.92527 N Lat, 109.40398 W Lon		
 Distance in miles and direction from nearest town or post of 56.9 MILES SOUTH OF VERNAL, UTAH 	office*	12. County or Parish UINTAH	13. State UT
15. Distance from proposed location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 661	16. No. of Acres in Lease 320.00	17. Spacing Unit dedicated to	this well
 Distance from proposed location to nearest well, drilling, completed, applied for, on this lease, ft. 1220 	19. Proposed Depth 7100 MD	20. BLM/BIA Bond No. on fi NM 2308	ile
21. Elevations (Show whether DF, KB, RT, GL, etc. 5478 GL	22. Approximate date work will start	23. Estimated duration 45 DAYS	
	24. Attachments		
The following, completed in accordance with the requirements o	f Onshore Oil and Gas Order No. 1, shall be attached to t	his form:	
 Well plat certified by a registered surveyor. A Drilling Plan. A Surface Use Plan (if the location is on National Forest Systs SUPO shall be filed with the appropriate Forest Service Office of the Company of	Item 20 above).	ons unless covered by an existing formation and/or plans as may be	•
25. Signature (Electronic Submission)	Name (Printed/Typed) KAYLENE R GARDNER Ph: 435-781-9	111	Date 12/07/2007
Title LEAD REGULATORY ASSISTANT			
Approved by Signature	Name (Printed/Typed) RRADI FY G. HILL		Date 12 - (1)

Application approval does not warrant or certify the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Electronic Submission #57464 verified by the BLM Well Information System For EOG RESOURCES, INC., sent to the Vernal

ENVIRONMENTAL MANAGER


Federal Approval of this Action is Necessary

RECEIVED

DEC 1 1 2007

DIV. OF OIL, GAS & MINING

T10S, R22E, S.L.B.&M.



BASIS OF BEARINGS

BASIS OF BEARINGS IS A G.P.S. OBSERVATION.

(NAD 83)

LATITUDE = 39'55'30.98" (39.925272)

LONGITUDE = 109'24'14.32" (109.403978)

(NAD 27)

LATITUDE = 39.55'31.10'' (39.925306)


LONGITUDE = 109'24'11.87" (109.403297)

EOG RESOURCES, INC.

Well location, NBU #649-26E, located as shown in the NW 1/4 NE 1/4 of Section 26, T10S, R22E, S.L.B.&M., Uintah County, Utah.

BASIS OF ELEVATION

TWO WATER TRIANGULATION STATION LOCATED IN THE NW 1/4 OF SECTION 1, T10S, R21E, S.L.B.&M. TAKEN FROM THE BIG PACK MTN NE QUADRANGLE, UTAH, UINTAH COUNTY, 7.5 MINUTE SERIES (TOPOGRAPHICAL MAP) PUBLISHED BY THE UNITED STATES DEPARTMENT OF THE INTERIOR, GEOLOGICAL SURVEY. SAID ELEVATION IS MARKED AS BEING 5238 FEET.



UINTAH ENGINEERING & LAND SURVEYING

85 SOUTH 200 EAST - VERNAL, UTAH 84078

(435) 789-1017

SCALE 1" = 1000'	DATE SURVEYED: DATE DRAWN: 10-08-07 11-07-07		
J.M. K.F. L.K.	REFERENCES G.L.O. PLAT		
WEATHER COOL	FILE EOG RESOU	RCES, INC.	

LEGEND:

_ = 90° SYMBOL

= PROPOSED WELL HEAD

= SECTION CORNERS LOCATED

NATURAL BUTTES UNIT 649-26E NW/NE, SEC. 24, T10S, R22E, S.L.B.&M... UINTAH COUNTY, UTAH

1. & 2. ESTIMATED TOPS & ANTICIPATED OIL, GAS, & WATER ZONES:

FORMATION	TVD-RKB (ft)	Objective	Lithology	
Green River	948		Shale	
Wasatch	4,007	Primary	Sandstone	Gas
Chapita Wells	4,553	Primary	Sandstone	Gas
Buck Canyon	5,231	Primary	Sandstone	Gas
North Horn	5,911	Primary	Sandstone	Gas
KMV Price River	6,318	Primary	Sandstone	Gas
KMV Price River Middle	7,044		Sandstone	
TD	7,100			

Estimated TD: 7,100' or 200'± below Price River top

Anticipated BHP: 3,877 Psig

- 1. Fresh Waters may exist in the upper, approximately 1,000 ft \pm of the Green River Formation, with top at about 2,000 ft \pm .
- 2. Cement isolation is installed to surface of the well isolating all zones by cement.

3. PRESSURE CONTROL EQUIPMENT:

Production Hole – 5000 Psig

BOP schematic diagrams attached.

4. CASING PROGRAM:

CASING	<u>Hole</u> Size	<u>Length</u>	Size	WEIGHT	<u>Grade</u>	Thread	Rating Collapse	<u>Factor</u> Burst	Tensile
Conductor	17 ½"	0 – 45'	13 3/8"	48.0#	H-40	STC	770 PSI	1730 PSI	322,000#
Surface	12 1/4"	0' - 2,300' KB±	95/8''	36.0#	J-55	STC	2020 PSI	3520 Psi	394,000#
Production	7-7/8"	Surface – TD	4-1/2"	11.6#	N-80	LTC	6350 PSI	7780 Psi	233,000#

Note: 12-1/4" surface hole will be drilled to a total depth of 200'± below the base of the Green River lost circulation zone and cased w/9-5%" as shown to that depth. Drilled depth may be shallower or deeper than the 2300' shown above depending on the actual depth of the loss zone.

All casing will be new or inspected.

NATURAL BUTTES UNIT 649-26E NW/NE, SEC. 24, T10S, R22E, S.L.B.&M.. UINTAH COUNTY, UTAH

5. Float Equipment:

Surface Hole Procedure (0'- 2300'±)

Guide Shoe

Insert Float Collar (PDC drillable)

Centralizers: 1-5' above shoe, top of jts. #2 and #3 then every 5th joint to surface. (15 total)

Production Hole Procedure (2300'± - TD):

Float shoe, I joint casing, float collar and balance of casing to surface. 4-½", 11.6#, N-80 or equivalent marker collars or short casing joints to be placed at top of Price River and 400' above top of Wasatch. Centralizers to be placed 5' above shoe on joint #1, top of joint #2, and every 2nd joint to 400' above Wasatch Island top. Thread lock float shoe, top and bottom of float collar, and top of 2nd joint.

6. MUD PROGRAM

Surface Hole Procedure (Surface - 2300'±):

Air/air mist or aerated water.

<u>Production Hole Procedure (2300' \pm - TD):</u> Anticipated mud weight 9.5 – 10.5 ppg depending on actual wellbore conditions encountered while drilling.

2300'±-TD A closed mud system will be utilized. A bentonite gelled water mud system will be used to control viscosity w/PHPA polymer used for supplemental viscosity and clay encapsulation/inhibition. Water loss will be maintained at <15cc's using white starch or PAC. Bactericides will be used as needed. Anticipated pH will range from 9.0-10.0. Mud weight will be adjusted as necessary for well control. Deflocculants/thinners will be used as necessary to maintain mud quality. LCM sweeps will be utilized as necessary to control lost circulation and mud loss. CO2 contamination, if encountered, will be treated with lime and gypsum.

7. VARIANCE REQUESTS:

Reference: Onshore Oil and Gas Order No. 2 – Item E: Special Drilling Operations

EOG Resources, Inc. requests a variance to regulations requiring the blooie line to be 100' in length. Due to reduce location excavation, the blooie line will be approximately 75' in length

NATURAL BUTTES UNIT 649-26E NW/NE, SEC. 24, T10S, R22E, S.L.B.&M.. UINTAN COUNTY, UTAH

8. EVALUATION PROGRAM:

Logs:

Mud log from base of surface casing to TD.

Cased-hole Logs:

Cased-hole logs will be run in lieu of open-hole logs consisting of the following:

Cement Bond / Casing Collar Locator and Pulsed Neutron

9. CEMENT PROGRAM:

Surface Hole Procedure (Surface - 2300'±):

Lead:

185 sks Class "G" cement with 16% Gel, 10 #/sx Gilsonite, 3% Salt, 2% CaCI₂, 3 lb/sx GR3

½ #/sx Flocele mixed at 11 ppg. 3.82 ft³/sk. vield. 23 gps water.

Tail:

207 sks Class "G" cement with 2% CaCl₂, ½#/sk Flocele mixed at 15.6 ppg, 1.18 ft³/sk., 5.2

gps water.

Top Out: As necessary with Class "G" cement with 2% CaCl₂, ½#/sk Flocele mixed at 15.6 ppg, 1.18

ft³/sk., 5.2 gps water.

Note:

Cement volumes will be calculated to bring lead cement to surface and tail cement to

500'above the casing shoe.

Production Hole Procedure (2300'± - TD)

Lead:

97 sks: Hi-Lift "G" w/12% D20 (Bentonite), 1% D79 (Extender), 5% D44

(Salt), 0.2% D46 (Antifoam), 0.25% D112 (Fluid Loss Additive), 0.25 pps D29

(cello flakes) mixed at 11.0 ppg, 3.91 ft³/sk., 24.5 gps water.

Tail:

629 sks: 50:50 Poz "G" w/ 2% D20 (Bentonite), 0.1% D46 (Antifoam), 0.075% D13

(Retarder), 0.2% D167 (Fluid Loss Additive), 0.2% D65 (Dispersant), mixed at

14.1 ppg, $1.28 \text{ ft}^3/\text{sk.}$, 5.9gps water.

Note:

The above number of sacks is based on gauge-hole calculation.

Lead volume to be calculated to bring cement to 200'± above 9-5/8" casing shoe.

Tail volume to be calculated to bring cement to 400'± above top of Wasatch.

Final Cement volumes will be based upon gauge-hole plus 45% excess.

NATURAL BUTTES UNIT 649-26E NW/NE, SEC. 24, T10S, R22E, S.L.B.&M.. UINTAH COUNTY, UTAH

10. ABNORMAL CONDITIONS:

Surface Hole (Surface - 2300'±):

Lost circulation

Production Hole (2300'± - TD):

Sloughing shales, lost circulation and key seat development are possible in the Wasatch Formation.

11. STANDARD REQUIRED EQUIPMENT:

- A. Choke Manifold
- B. Upper and Lower Kelly Cock
- C. Stabbing Valve
- D. Visual Mud Monitoring


12. HAZARDOUS CHEMICALS:

No chemicals subject to reporting under SARA title III in an amount equal to or greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling of this well. Furthermore, no extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities, will be used, produced, stored, transported, or disposed of in association with the drilling of this well.

(Attachment: BOP Schematic Diagram)


EOG RESOURCES 11" 5,000 PSI W.P. BOP CONFIGURATION

PAGE 1 OF 2



EOG RESOURCES CHOKE MANIFOLD CONFIGURATION W/ 5,000 PSI WP VALVES

PAGE 2 0F 2



4" 5,000 PSI CHOKE LINE FROM HCR VALVE

Testing Procedure:

- 1. BOP will be tested with a professional tester to conform to Onshore Order #2.
- 2. Blind and Pipe rams will be tested to rated working pressure, 5,000 psi.
- 3. Annular Preventer will be tested to 50% working pressure, 2,500 psi. Casing will be tested to 0.22 psi / ft. or 1,500 psi. Not to exceed 70% of burst strength, whichever is greater.
- 4. All lines subject to well pressure will be tested to the same pressure as blind and pipe rams.
- 5. All BOPE specifications and configurations will meet Onshore Order #2 requirements.



Natural Buttes Unit 649-26E NWNE, Section 26, T10S, R22E Uintah County, Utah

SURFACE USE PLAN

The well pad is approximately 400 feet long with a 221-foot width, containing 2.03 acres more or less. The well access road is approximately 330 feet long with a 40-foot right-of-way, disturbing approximately 0.30 acres. New surface disturbance associated with access road and the well pad is estimated to be approximately 2.33 acres. The pipeline is approximately 161 feet long with a 40-foot right-of-way, disturbing approximately 0.15 acres.

1. EXISTING ROADS:

- A. See attached Plats showing directional reference stakes on location, and attached TOPO Map "B" showing access to location from existing roads.
- B. The proposed well site is located approximately 56.9 miles south of Vernal, Utah See attached TOPO Map "A".
- C. Refer to attached Topographic Map "A" showing labeled access route to location.
- D. Existing roads will be maintained and repaired as necessary.

2. PLANNED ACCESS ROAD:

- A. The access road will be approximately 330' in length, Culvert's if necessary See attached Topo B.
- B. The access road has a 40-foot ROW w/18 foot running surface.
- C. Maximum grade of the new access road will be 8 percent.
- D. No turnouts will be required.
- E. Road drainage crossings shall be of the typical dry creek drainage crossing type.
- F. No bridges, or major cuts and fills will be required.
- G. The access road will be dirt surface.
- H. No gates, cattleguards, or fences will be required or encountered.

- I. A 40-foot permanent right-of-way is requested. No surfacing material will be used.
- J. No additional storage areas will be needed for storing equipment, stockpiling, or vehicle parking.

All travel will be confined to existing access road rights-of-way.

New or reconstructed roads will be centerlined – flagged at time of location staking. Access roads and surface disturbing activities will conform to standards outlined in the Bureau of Land Management and Forest Service publication: Surface Operating Standards for Oil and Gas Exploration and Development, Fourth Edition and/or BLM Manual Section 9113 concerning road construction standards on projects subject to federal jurisdiction.

The road shall be constructed/upgraded to meet the standards of the anticipated traffic flow and all-weather road requirements. Construction/upgrading shall include ditching, draining, graveling, crowning, and capping the roadbed as necessary to provide a well constructed safe road. Prior to upgrading, the road shall be cleared of any snow cover and allowed to dry completely. Traveling off the 40-foot right-of-way will not be allowed. Road drainage crossings shall be of the typical dry creek drainage crossing type. Crossings shall be designed so they will not cause siltation or accumulation of debris in the drainage crossing nor shall the roadbed block the drainages. Erosion of drainage ditches by runoff water shall be prevented by diverting water off at frequent intervals by means of cutouts. Upgrading shall not be allowed during muddy conditions. Should mud holes develop, they shall be filled in and detours around then avoided.

As operator, EOG Resources, Inc. shall be responsible for all maintenance on cattleguards, or gates associated with this oil and/or gas operation.

Traveling off the 40-foot right-of-way will not be allowed. The access road and associated drainage structures will be constructed and maintained in accordance with road guidelines contained in the joint BLM/USFS publication: Surface Operating Standards for Oil and Gas Exploration and Development, Fourth Edition, and/or BLM Manual Section 9113 concerning road construction standards on projects subject to federal jurisdiction. During the drilling and production phase of operations, the road surface and shoulders will be kept in a safe and useable condition and drainage ditches and culverts will be kept clear and free flowing.

No off lease right-of-way will be required. The entire length of the proposed access road is located within lease and within the Natural Buttes Unit.

3. LOCATION OF EXISTING WELLS WITHIN A ONE-MILE RADIUS:

See attached TOPO map "C" for the location of wells within a one-mile radius.

4. LOCATION OF EXISTING AND/OR PROPOSED PRODUCTION FACILITIES:

A. On Well Pad

- Production facilities will be set on location if the well is successfully completed for production. Facilities will consist of wellhead valves, combo separator-dehy unit with meter, two (2) 400-bbl vertical tanks and attaching piping.
- 2. Gas gathering lines A 4" gathering line will be buried from dehy to the edge of the location.

B. Off Well Pad

- 1. Proposed pipeline will transport natural gas.
- 2. The pipeline will be a permanent feeder line.
- 3. The length of the proposed pipeline is 161' x 40'. The proposed pipeline leaves the eastern edge of the well pad (Lease U-472) proceeding in a northerly direction for an approximate distance of 161' tieing into an existing pipeline in the NWNE of Section 26, T10S, R22E (Lease U472). Pipe will be 4" NOM, 0.156 wall, Grade X42, Zap-Lock, electric weld with a 35 mil X-Tru coating.
- 4. Proposed pipeline will be a 4" OD steel, zap-lok line laid on the surface
- 5. Proposed pipeline will be laid on surface.
- A 20-foot permanent pipeline right-of-way is requested. A 40-foot temporary
 pipeline right-of-way for construction purposes is requested, the temporary rightof-way will be utilized for a 10-day period.
- 7. The proposed pipeline route begins in the NWNE of section 26, township 10S, range 22E, proceeding northerly for an approximate distance of 161' to the NWNE of section 26, township 10S, range 22E.
- 8. Pipeline will be coupled using the Zap lock method. No additional off-pad facilities will be required.

All permanent (on site for six months or longer) structures constructed or installed (including pumping units) will be painted a flat, non-reflective, earthtone color to match one of the standard environmental colors, as determined by the Rocky Mountain Five State Interagency Committee. All facilities will be painted within 6 months of installation. All facilities will be painted with Carlsbad Canyon. Facilities required to comply with O.S.H.A. (Occupational Safety and Health Act) will be excluded.

5. LOCATION AND TYPE OF WATER SUPPLY:

- A. Water supply will be from Bonanza Power Plant water source in Sec 26, T8S, R23E, Uintah County, UT (State Water Right # 49-225(A31368)). Water will be hauled by a licensed trucking company.
- B. Water will be hauled by a licensed trucking company.
- C. No water well will be drilled on lease.

6. SOURCE OF CONSTRUCTION MATERIALS:

- A. All construction material for this pipeline will be of native borrow and soil accumulated during the construction of the location.
- B. No mineral materials will be required.

7. METHODS OF HANDLING WASTE DISPOSAL:

A. METHODS AND LOCATION

- 1. Cuttings will be confined in the reserve pit.
- 2. A portable toilet will be provided for human waste during the drilling and completion of the well. Disposal will be at the Vernal sewage disposal plant.
- 3. Burning will not be allowed. Trash and other waste material will be contained in a wire mesh cage and disposed of at the Uintah County Landfill.
- 4. Produced wastewater will be confined to a lined pit or storage tank for a period not to exceed 90 days after initial production. After the 90 day period, the produced water will be contained in a tank on location and then disposed of at one of the following locations: Natural Buttes Unit 21-20B SWD, Ace Disposal, CWU 550-30N SWD, CWU 2-29 SWD, Red Wash Evaporation Ponds 1, 2, 3, 4 and 5, or EOG Resources, Inc. drilling operations (Chapita Wells Unit, Natural Buttes Unit & Stagecoach Unit).
- All chemicals will be disposed of at an authorized disposal site. Drip pans and absorbent pads will be used on the drilling rig to avoid leakage of oil to the pit.
- B. Water from drilling fluids and recovered during testing operations will be disposed of by either evaporating in the reserve pit, through natural or artificial methods, or removed and disposed of at an authorized disposal site. Introduction of well bore hydrocarbons to the reserve pit will be avoided by flaring them off in the flare pit at the time of recovery.

The reserve pit will be constructed so as not to leak, break, or allow discharge. If the reserve pit requires padding prior to lining (due to rocky conditions) felt padding will be used.

The reserve pit shall be lined with **double felt, and a 20-millimeter plastic liner.**Sufficient bedding (i.e. weed free straw, or hay; felt; polyswell or soil) will be used to cover any rocks. The liner will overlap the pit walls and be covered with dirt and/or rocks to hold it in place. No trash, scrap pipe, etc., that could puncture the liner will be disposed of in the pit. More stringent protective requirements may be deemed necessary by the A.O.

EOG Resources, Inc. maintains a file, per 29 CFR 1910.1200 (g) containing current Material Safety Data Sheets (MSDS) for all chemicals, compounds, and/or substances which are used during the course of construction, drilling, completion, and production operations for this project. Hazardous materials (substances) which may be found at the site may include drilling mud and cementing products which are primarily inhalation hazards, fuels (flammable and/or combustible), materials that may be necessary for well completion/ stimulation activities such as flammable or combustible substances and acids/gels (corrosives). The opportunity for Superfund Amendments and Reauthorization Act (SARA) listed Extremely Hazardous Substances (EHS) at the site is generally limited to proprietary treating chemicals. All hazardous and EHS and commercial preparations will be handled in an appropriate manner to minimize the potential for leaks or spills to the environment.

No chemicals subject to reporting under SARA Title III (hazardous materials) in an amount greater than 10,000 pounds will be used, produced, stored, transported, or disposed of annually in association with the drilling, testing, or completion of the well. Furthermore, extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities, will not be used, produced, stored, transported, or disposed of in association with the drilling, testing or completion of the well.

8. ANCILLARY FACILITIES:

None anticipated.

9. WELL SITE LAYOUT:

- A. Refer to attached well site plat for related topography cuts and fills and cross sections.
- B. Refer to attached well site plat for rig layout and soil material stockpile location as approved on On-site.
- C. Refer to attached well site plat for rig orientation, parking areas, and access road.

The reserve pit will be located on the east corner of the location. The flare pit will be located downwind of the prevailing wind direction on the south side of the location, a minimum of 100 feet from the wellhead and 30 feet from the reserve pit fence.

The stockpiled pit topsoil (first six inches) will be stored separate from the location topsoil. The stockpiled location topsoil will be stored in a location providing easy access for interim reclamation and protection of the topsoil. Upon completion of construction, the stockpiled

topsoil from the location will be broadcast seeded with the approved seed mixture from this location and then walked down with a Caterpillar tractor.

Access to the well pad will be from the south.

FENCING REQUIREMENTS:

All pits will be fenced according to the following minimum standards:

- A. Thirty-nine inch net wire shall be used with at least one strand of barbed wire on top of the net wire. (Barbed wire is not necessary if pipe or some type of reinforcement rod is attached to the top of the entire fence.)
- B. The net wire shall be no more than 2 inches above the ground. The barbed wire strand shall be 3 inches above the net wire. Total height of the fence shall be at least 42 inches.
- C. Corner posts shall be cemented and/or braced in such a manner as to keep the fence tight at all times.
- D. Standard steel, wood, or pipe posts shall be used between the corner braces. Maximum distances between any two posts shall be no greater than 16 feet.
- E. All wire shall be stretched by using a stretching device before it is attached to the corner posts.

The reserve pit fencing will be on the three sides during drilling operations and on the fourth side when the rig moves off location. Pits will be fenced and maintained until clean-up.

Each existing fence to be crossed by the access road shall be braced and tied off before cutting so as to prevent slacking of the wire. The opening shall be closed temporarily as necessary during construction to prevent the escape of livestock, and, upon completion of construction, the fence shall be repaired to BLM or SMA specifications. A cattleguard with an adjacent 16 foot gate shall be installed in any fence where a road is regularly traveled. If the well is a producer, the cattleguards (shall/shall not) be permanently counted on concrete bases. Prior to crossing any fence located on Federal land, or any fence between Federal land and private land, the operator will contact the BLM, who will in turn contact the grazing permittee or owner of said fence and offer him/her the opportunity to be present when the fence is cut in order to satisfy himself/herself that the fence is adequately braced and tied off.

10. Plans for Reclamation of the Surface:

A. Interim Reclamation (Producing Location)

Immediately upon well completion, the location and surrounding area will be cleared of all unused tubing, equipment, debris, materials, trash, and junk not required for production.

Immediately upon well completion, any hydrocarbons on the pit shall be removed in accordance with CFR 3162.7-1.

If a plastic nylon reinforced liner is used, it shall be torn and perforated before backfilling of the reserve pit.

The reserve pit and that portion of the location not needed for production facilities/operations will be recontoured to the approximate natural contours. The reserve pit will be reclaimed within 90 days from the date of the well completion, or as soon as environmental conditions allow. Before any dirt takes place, the reserve pit must be completely dry and free of all foreign obstacles.

The stockpiled pit topsoil will then be spread over the pit area and broadcast seeded with the prescribed seed mixture for this location. The seeded area will then be walked down with a cat.

Seed Mixture	Drilled Rate (lbs./acre PLS*)
HyCrest Wheatgrass	9.0
Prostrate Kochia	3.0

^{*}Pure live seed (PLS) formula: percent of purity of seed mixture times percent germination of seed mixture equals portion of seed mixture that is PLS.

B. Dry Hole/Abandoned Location

At such time as the well is plugged and abandoned, the operator will submit a subsequent report of abandonment and the BLM will attach the appropriated surface rehabilitation conditions of approval.

Seed Mixture	Drilled Rate (lbs./acre PLS*)
Wyoming Big Sage	3.0
Shadscale	3.0
Needle and Threadgrass	3.0
HyCrest Wheatgrass	1.0
Scarlet Globe Mallow	1.0

^{*}Pure live seed (PLS) formula: percent of purity of seed mixture times percent germination of seed mixture equals portion of seed mixture that is PLS.

11. SURFACE OWNERSHIP:

Surface ownership of the proposed well site, access road, and pipeline route is as follows:

Bureau of Land Management

12. OTHER INFORMATION:

- A. EOG Resources, Inc. will inform all persons in the area who are associated with this project that they are subject to prosecution for knowingly disturbing historic or archaeological sites, or for collecting artifacts. If historic or archaeological materials are uncovered during construction, the operator will immediately stop work that might further disturb such materials, and contact the Authorized Officer. Within five working days the Authorized Officer will inform the operator as to:
 - Whether the materials appear eligible for the National Register of Historic Places;
 - The mitigation measures the operator will likely have to undertake before the site can be used.
 - A time frame for the Authorized Officer to complete an expedited review under 36 CFR 800.11 to confirm, through the State Historic Preservation Officer, that the findings of the Authorized Officer are correct and that mitigation is appropriate.

If the operator wished, at any time, to relocate activities to avoid the expense of mitigation and/or the delays associated with this process, the Authorized Officer will assume responsibility for whatever recordation and stabilization of the exposed materials that may be required. Otherwise, the operator will be responsible for mitigation costs. The Authorized Officer will provide technical and procedural guidelines for the conduct of mitigation. Upon verification from the Authorized Officer that required mitigation has been completed, the operator will then be allowed to resume construction.

- B. As operator, EOG Resources, Inc. will control noxious weeds along Right-of-Ways for roads, pipelines, well sites, or other applicable facilities. A list of noxious weeds will be obtained from the BLM administered land, a Pesticide Use proposal shall be submitted, and given approval, prior to the application or herbicides or other pesticides or possible hazardous chemicals.
- C. Drilling rigs and/or equipment used during drilling operations on this well site will not be stacked or stored on BLM lands after the conclusion of drilling operations or at any other time without BLM authorization. However, if BLM authorization is obtained, it is only a temporary measure to allow time to make arrangements for permanent storage on commercial facilities. (The BLM does not seek to compete with private industry. There are commercial facilities available for stacking and storing drilling rigs.)
- D. The drilling rig and ancillary equipment will be removed from the location prior to commencement of completion operations. Completion operations will be conducted utilizing a completion/workover rig.

All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws, regulations, Onshore Oil and Gas Orders, the approved Plan of Operations, and any applicable Notice of Lessees. The operator is fully responsible for the actions of its subcontractors. A complete copy of the approved "Application for Permit to Drill" will be furnished to the field representative(s) to ensure compliance and shall be on location during all construction and drilling operations.

Construction activity will not be conducted using frozen or saturated soils material or during periods when watershed damage is likely to occur.

If the existing access road, proposed access road, and proposed pad are dry during construction, drilling, and completion activities, water will be applied to help facilitate compaction during construction and to minimize soil loss as a result of wind erosion.

A cultural resources survey was conducted and will be submitted by Montgomery Archeological Consultants. A paleontological survey was conducted and will be submitted by Intermountain Paleontological.

LESSEE OR OPERATOR'S REPRESENTATIVE AND CERTIFICATION:

PERMITTING AGENT

Kaylene R. Gardner EOG Resources, Inc. P.O. Box 1815 Vernal, UT 84078 (435) 781-9111

All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws, regulations, Onshore Oil and Gas Orders, the approved plan of operations, and any applicable Notice to Lessees. The operator is fully responsible for the actions of his subcontractors. A copy of these conditions will be furnished to the field representative to insure compliance.

The operator or his/her contractor shall contact the BLM office at (435) 781-4400 forty-eight (48) hours prior to construction activities.

CERTIFICATION:

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drill site and access route; that I am familiar with the conditions which currently exist; that the statements made in this plan are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by EOG Resources, Inc. and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 U.S.C. 1001 for the filing of a false statement.

Please be advised that EOG Resources, Inc. is considered to be the operator of the Natural Buttes Unit 649-26E Well, located in the NWNE, of Section 26, T10S, R22E, Uintah County, Utah; Federal land and minerals; and is responsible under the terms and conditions of the lease for the operations conducted upon the leased lands. Bond Coverage is under Bond # NM 2308.

December 7, 2007

Date

Caylene R. Gardner, Lead Regulatory Assistant

EOG RESOURCES, INC.

NBU #649-26E

LOCATED IN UINTAH COUNTY, UTAH SECTION 26, T10S, R22E, S.L.B.&M.



PHOTO: VIEW FORM CORNER #5 TO LOCATION STAKE

CAMERA ANGLE: WESTERLY




PHOTO: VIEW OF BEGINNING OF PROPOSED ACCESS

CAMERA ANGLE: NORTHEASTERLY





PIPELINE PHOTOS		10 24 07 MONTH DAY YEAR		РНОТО	
TAKEN BY: D.K.	DRAWN BY: Z.I	. REV	ISED: (0-00-00	


EOG RESOURCES, INC. NBU #649-26E SECTION 26, T10S, R22E, S.L.B.&M.


PROCEED IN A WESTERLY DIRECTION FROM VERNAL, UTAH ALONG U.S. HIGHWAY 40 APPROXIMATELY 14.0 MILES TO THE JUNCTION OF STATE HIGHWAY 88; EXIT LEFT AND PROCEED IN A SOUTHERLY DIRECTION APPROXIMATELY 17.0 MILES TO OURAY, UTAH; PROCEED IN A SOUTHERLY, THEN SOUTHEASTERLY DIRECTION APPROXIMATELY 11.2 MILES ON THE SEEP RIDGE ROAD TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE EAST; TURN LEFT AND PROCEED IN AN EASTERLY, THEN SOUTHEASTERLY DIRECTION APPROXIMATELY 9.6 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE EAST; TURN LEFT AND PROCEED IN AN EASTERLY, THEN NORTHEASTERLY DIRECTION APPROXIMATELY 2.6 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE NORTHEAST; TURN RIGHT AND PROCEED IN A NORTHEASTERLY, THEN SOUTHERLY DIRECTION APPROXIMATELY 0.7 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE SOUTHEAST; TURN LEFT AND PROCEED IN A SOUTHEASTERLY, THEN NORTHEASTERLY DIRECTION APPROXIMATELY 1.3 MILES TO THE JUNCTION OF THIS ROAD AND AN EXISTING ROAD TO THE NORTH; TURN LEFT AND PROCEED IN A NORTHERLY DIRECTION APPROXIMATELY 0.15 MILES TO THE BEGINNING OF THE PROPOSED ACCESS ROAD FOR THE #613-23 TO THE NORTHEAST; FOLLOW ROAD FLAGS IN A NORTHEASTERLY DIRECTION APPROXIMATELY 0.15 MILES TO THE BEGINNING OF THE PROPOSED ACCESS TO THE NORTH; FOLLOW ROAD FLAGS IN A NORTHERLY DIRECTION APPROXIMATELY 330' TO THE PROPOSED LOCATION.


TOTAL DISTANCE FROM VERNAL, UTAH TO THE PROPOSED WELL LOCATION IS APPROXIMATELY 56.85 MILES.


















APD RECEIVED: 12/11/2007	API NO. ASSIGNED: 43-047-39870
WELL NAME: NBU 649-26E OPERATOR: EOG RESOURCES, INC. (N9550) CONTACT: KAYLENE GARDNER	PHONE NUMBER: 435-781-9111
PROPOSED LOCATION:	INSPECT LOCATN BY: / /
NWNE 26 100S 220E SURFACE: 0661 FNL 1759 FEL	Tech Review Initials Date
BOTTOM: 0661 FNL 1759 FEL	Engineering
COUNTY: UINTAH LATITUDE: 39.92526 LONGITUDE: -109.4032	Geology
UTM SURF EASTINGS: 636455 NORTHINGS: 44204	73 Surface
LEASE TYPE: 1 - Federal LEASE NUMBER: UTU472 SURFACE OWNER: 1 - Federal RECEIVED AND/OR REVIEWED:	PROPOSED FORMATION: WSMVD COALBED METHANE WELL? NO LOCATION AND SITING:
Plat	The second of t
STIPULATIONS:	cQ
2-011	PHALE







MICHAEL R. STYLER
Executive Director

Division of Oil Gas and Mining

JOHN R. BAZA
Division Director

December 17, 2007

EOG Resources, Inc. 1060 East Highway 40 Vernal, UT 84078

Re:

Natural Buttes Unit 649-26E Well, 661' FNL, 1759' FEL, NW NE, Sec. 26, T. 10 South,

R. 22 East, Uintah County, Utah

Gentlemen:

Pursuant to the provisions and requirements of Utah Code Ann.§ 40-6-1 et seq., Utah Administrative Code R649-3-1 et seq., and the attached Conditions of Approval, approval to drill the referenced well is granted.

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date. The API identification number assigned to this well is 43-047-39870.

Sincerely,

Gil Hunt

Associate Director

pab Enclosures

cc:

Uintah County Assessor

Bureau of Land Management, Vernal Office



Location: NW NE	Sec. 26 T. 10	South	R.	22 East
Lease:	 UTU472			
API Number:	43-047-39870			
Well Name & Number	 Natural Buttes Unit 649-26E		i i i i i i i i i i i i i i i i i i i	
Operator:	 EOG Resources, Inc.		· · · · · · · · · · · · · · · · · · ·	

Conditions of Approval

1. General

Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for permit to drill.

2. Notification Requirements

Notify the Division within 24 hours of spudding the well.

• Contact Carol Daniels at (801) 538-5284.

Notify the Division prior to commencing operations to plug and abandon the well.

• Contact Dustin Doucet at (801) 538-5281 office (801) 733-0983 home

3. Reporting Requirements

All required reports, forms and submittals will be promptly filed with the Division, including but not limited to the Entity Action Form (Form 6), Report of Water Encountered During Drilling (Form 7), Weekly Progress Reports for drilling and completion operations, and Sundry Notices and Reports on Wells requesting approval of change of plans or other operational actions.

- 4. State approval of this well does not supersede the required federal approval, which must be obtained prior to drilling.
- 5. In accordance with Order in Cause No. 190-5(b) dated October 28, 1982, the Operator shall comply with requirements of Rules R649-3-31 and R649-3-27 pertaining to Designated Oil Shale Areas. Additionally, the operator shall ensure that the surface and/or production casing is properly cemented over the entire oil shale interval as defined by Rule R649-3-31. The Operator shall report the actual depth the oil shale is encountered to the Division.

STATE OF UTAH	FORM 9				
DEPARTMENT OF NATURAL RESOURCES DIVISION OF OIL, GAS AND MINING	5. LEASE DESIGNATION AND SERIAL NUMBER: UTU-472				
SUNDRY NOTICES AND REPORTS ON WELLS	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:				
Do not use this form for proposals to drill new wells, significantly deepen existing wells below current bottom-hole depth, reenter plugged wells, or to drill horizontal laterals. Use APPLICATION FOR PERMIT TO DRILL form for such proposals.	7. UNIT OF CA AGREEMENT NAME: Natural Buttes				
1. TYPE OF WELL OIL WELL GAS WELL OTHER	8. WELL NAME and NUMBER: Natural Buttes Unit 649-26E				
2. NAME OF OPERATOR: EOG Resources, Inc.	9. API NUMBER: 43-047-39870				
3. ADDRESS OF OPERATOR: PHONE NUMBER: (435) 789-0790	10. FIELD AND POOL, OR WILDCAT: Natural Buttes				
4. LOCATION OF WELL					
FOOTAGES AT SURFACE: 661' FNL & 1759' FEL 39.925272 LAT 109.403978 LON	county: Uintah				
QTR/QTR, SECTION, TOWNSHIP, RANGE, MERIDIAN: NWNE 26 10S 22E S.L.B. & M.	STATE: UTAH				
11. CHECK APPROPRIATE BOXES TO INDICATE NATURE OF NOTICE, REPO	ORT, OR OTHER DATA				
TYPE OF SUBMISSION TYPE OF ACTION					
NOTICE OF INTENT (Submit in Duplicate) ALTER CASING DEEPEN FRACTURE TREAT	REPERFORATE CURRENT FORMATION				
Approximate date work will start: CASING REPAIR NEW CONSTRUCTION	SIDETRACK TO REPAIR WELL TEMPORARILY ABANDON				
CHANGE TO PREVIOUS PLANS OPERATOR CHANGE	TUBING REPAIR				
CHANGE TUBING PLUG AND ABANDON	VENT OR FLARE				
SUBSEQUENT REPORT CHANGE WELL NAME PLUG BACK	WATER DISPOSAL				
(Submit Original Form Only) CHANGE WELL STATUS PRODUCTION (START/RESUME)	WATER SHUT-OFF				
Date of work completion: COMMINGLE PRODUCING FORMATIONS RECLAMATION OF WELL SITE	✓ OTHER: APD EXTENSION				
CONVERT WELL TYPE RECOMPLETE - DIFFERENT FORMATION	REQUEST				
12. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. Clearly show all pertinent details including dates, depths, volumes, etc. EOG Resources, Inc. respectfully requests the APD for the referenced well be extended for one year. Approved by the Utah Division of Oil, Gas and Mining Date: 12.01-06 By:					
NAME (PLEASE PRINT) Mickenzie Thacker TITLE Operations Clerk					
SIGNATURE Willer Thau DATE 11/24/2008					

COPY SENT TO OPERATOR

(See Instructions on Reverse Side)

RECEIVED

NOV 2 6 2008

DIV. OF OIL, GAS & MINING

(5/2000)

Application for Permit to Drill Request for Permit Extension Validation

(this form should accompany the Sundry Notice requesting permit extension)

API:

43-047-39870

Well Name: Natural Buttes Unit 649-26E Location: 661 FNL & 1759 FEL (NWNE), SECTION 26, 1 Company Permit Issued to: EOG RESOURCES, INC. Date Original Permit Issued: 12/17/2007	Γ10S, R22E S.L.B.&M
The undersigned as owner with legal rights to drill on tabove, hereby verifies that the information as submitted approved application to drill, remains valid and does n	ed in the previously
Following is a checklist of some items related to the appreciated.	oplication, which should be
If located on private land, has the ownership changed, agreement been updated? Yes⊟No⊟	, if so, has the surface
Have any wells been drilled in the vicinity of the proporthe spacing or siting requirements for this location? Ye	
Has there been any unit or other agreements put in pla permitting or operation of this proposed well? Yes⊡N	
Have there been any changes to the access route inclof-way, which could affect the proposed location? Yes	
Has the approved source of water for drilling changed	? Yes□No☑
Have there been any physical changes to the surface which will require a change in plans from what was dis evaluation? Yes□No☑	
s bonding still in place, which covers this proposed we	ell? Yes⊠No□
Midumu Trayw ") Signature	11/24/2008
Signature	Date
Title: Operations Clerk	
Representing: EOG Resources, Inc.	

NUV 2 6 2008
DIV. OF OIL, GAS & MINING

Form 316 -3 (August 2007)

RECEIVED

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

DEC 0 7 2007

FORM APPROVED OMB No. 1004-0136 Expires July 31, 2010

UTU472

APPLICATION FOR PERI	III TO DRILL OR REENTER DLV	6. If Indian, Anottee of Tribe Name
1a. Type of Work: 🛛 DRILL 🔲 REENTER		7. If Unit or CA Agreement, Name and No. UTU63047A
		8. Lease Name and Well No.
ib. Type of Well: ☐ Oil Well 🔀 Gas Well	Other Single Zone Multiple Zone	NBU 649-26E
	ntact: KAYLENE R GARDNER AYLENE_GARDNER@EOGRESOURCES.COM	9. APT Well No. 3987D
3a. Address 1060 EAST HIGHWAY 40 VERNAL, UT 84078	3b. Phone No. (include area code) Ph: 435-781-9111	10. Field and Pool, or Exploratory NATURAL BUTTES
4. Location of Well (Report location clearly and in ac	cordance with any State requirements.*)	11. Sec., T., R., M., or Blk. and Survey or Area
At surface NWNE 661FNL 1759I At proposed prod. zone NWNE 661FNL 1759I	FEL 39.92527 N Lat, 109.40398 W Lon FEL 39.92527 N Lat, 109.40398 W Lon	Sec 26 T10S R22E Mer SLB SME: BLM
 Distance in miles and direction from nearest town or p MILES SOUTH OF VERNAL, UTAH 	ost office*	12. County or Parish 13. State UINTAH UT
15. Distance from proposed location to nearest property of lease line, ft. (Also to nearest drig. unit line, if any) 661	16. No. of Acres in Lease 320.00	17. Spacing Unit dedicated to this well
		30 01 W/BIA Day 4 Viz. on 4 In
 Distance from proposed location to nearest well, drilling completed, applied for, on this lease, ft. 1220 	ng, 19. Proposed Depth 7100 MD	20. BLM/BIA Bond No. on file NM2308
21. Elevations (Show whether DF, KB, RT, GL, etc. 5478 GL	22. Approximate date work will start	23. Estimated duration 45 DAYS
	24. Attachments	
The following, completed in accordance with the requirement	ts of Onshore Oil and Gas Order No. 1, shall be attached to thi	s form:
 Well plat certified by a registered surveyor. A Drilling Plan. A Surface Use Plan (if the location is on National Forest SUPO shall be filed with the appropriate Forest Service) 	System Lands, the Item 20 above). 5. Operator certification	ons unless covered by an existing bond on file (see formation and/or plans as may be required by the
25. Signature (Electronic Submission)	Name (Printed/Typed) KAYLENE R GARDNER Ph: 435-781	-9111 Date 12/07/2007
Title LEAD REGULATORY ASSISTANT		
Approved by (Signature)	Name (Printed/Typed) Teles Kenzela	DEC 2 4 2008
Assistant Field Manager Lands & Mineral Resources	Office VERNAL FIELD OFFI	
Application approval does not warrant or certify the applicate operations thereon. Conditions of approval, if any, are attached.	it holds legal or equitable title to those rights in the subject least IDITIONS OF APPR	e which would entitle the applicant to conduct OVAL ATTACHED

Electronic Submission #57464 verified by the BLM Well Information System For EOG RESOURCES INC, sent to the Vernal Committed to AFMSS for processing by GAIL JENKINS on 12/10/2007 (08GXJ1032AE)

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

DEC 3 0 2008

** BLM REVISED **

NOS-11/16/2007 08 CXS 00 43 AE



UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT VERNAL FIELD OFFICE

VERNAL FIELD OFFICE VERNAL, UT 84078

(435) 781-4400



CONDITIONS OF APPROVAL FOR APPLICATION FOR PERMIT TO DRILL

Company: EOG Resources, Inc. Location: NWNE, Sec. 26, T10S, R22E

Well No: NBU 649-26E Lease No: UTU-472

API No: 43-047-39870 Agreement: Natural Buttes Unit

Title	Name	Office Phone Number	Cell Phone Number
Petroleum Engineer:	Matt Baker	(435) 781-4490	(435) 828-4470
Petroleum Engineer:	Michael Lee	(435) 781-4432	(435) 828-7875
Petroleum Engineer:	Ryan Angus	(435) 781-4430	(435) 828-7368
Supervisory Petroleum Technician:	Jamie Sparger	(435) 781-4502	(435) 828-3913
Supervisory NRS:	Karl Wright	(435) 781-4484	(435) 828-7381
NRS/Enviro Scientist:	Holly Villa	(435) 781-4404	(435) 828-3544
NRS/Enviro Scientist:	James Hereford	(435) 781-3412	
NRS/Enviro Scientist:	Chuck Macdonald	(435) 781-4441	(435) 828-7481
NRS/Enviro Scientist:	Dan Emmett	(435) 781-3414	
NRS/Enviro Scientist:	Paul Percival	(435) 781-4493	
NRS/Enviro Scientist:	Anna Figueroa	(435) 781-3407	(435) 828-3548
NRS/Enviro Scientist:	Verlyn Pindell	(435) 781-3402	(435) 828-3547
NRS/Enviro Scientist:	Nathan Packer	(435) 781-3405	(435) 828-3545
NRS/Enviro Scientist:	David Gordon	(435) 781-4424	

Fax: (435) 781-3420

A COPY OF THESE CONDITIONS SHALL BE FURNISHED TO YOUR FIELD REPRESENTATIVE TO INSURE COMPLIANCE

All lease and/or unit operations are to be conducted in such a manner that full compliance is made with the applicable laws, regulations (43 CFR Part 3160), and this approved Application for Permit to Drill including Surface and Downhole Conditions of Approval. The operator is considered fully responsible for the actions of his subcontractors. A copy of the approved APD must be on location during construction, drilling, and completion operations. This permit is approved for a two (2) year period, or until lease expiration, whichever occurs first. An additional extension, up to two (2) years, may be applied for by sundry notice prior to expiration.

NOTIFICATION REQUIREMENTS

Location Construction	-	Forty-Eight (48) hours prior to construction of location and	
(Notify Environmental Scientist)		access roads.	
Location Completion	-	Prior to moving on the drilling rig.	
(Notify Environmental Scientist)			
Spud Notice	-	Twenty-Four (24) hours prior to spudding the well.	
(Notify Petroleum Engineer)			
Casing String & Cementing	-	Twenty-Four (24) hours prior to running casing and cementing	
(Notify Supv. Petroleum Tech.)	į	all casing strings.	
BOP & Related Equipment Tests	-	- Twenty-Four (24) hours prior to initiating pressure tests.	
(Notify Supv. Petroleum Tech.)	-		
First Production Notice	-	- Within Five (5) business days after new well begins or	
(Notify Petroleum Engineer)		production resumes after well has been off production for more	
		than ninety (90) days.	

COAs: Page 2 of 7 Well: NBU 649-26E

SURFACE USE PROGRAM CONDITIONS OF APPROVAL (COAs)

- If there is an active Gilsonite mining operation within 2 miles of the well location, operator shall notify the Gilsonite operator at least 48 hours prior to any blasting during construction.
- If paleontological materials are uncovered during construction, the operator is to immediately stop work and contact the Authorized Officer (AO). A determination will be made by the AO as to what mitigation may be necessary for the discovered paleontologic material before construction can continue.

SITE SPECIFIC COAs:

- Prevent fill and stock piles from entering drainages, ESPECIALLY ON THE WEST SIDE OF LOCATION.
- The access road shall be crowned and ditched. Flat-bladed roads are not allowed.
- The authorized officer may prohibit surface disturbing activities during severe winter, wet, or muddy conditions to minimize watershed damage. This limitation does not apply to operation and maintenance of producing wells.
- If additional erosion occurs during the life of this project, more culverts, low water crossings, berms, wing ditches, or gravel (from a private or commercial source) etc. shall be needed to control the erosion. Low-water crossings and culverts shall be appropriately constructed to avoid sedimentation of drainage ways and other water resources.
- Bury pipelines at all low water crossings.
- Surface pipelines will be placed 5-10 feet outside of the borrow area.
- Surface pipelines will be placed in such a way that they will not wander into the borrow area.
- Pipelines will be buried at all major road and drainage crossings.
- The pit liner is to be cut 5 feet below ground surface or at the level of the cuttings, whichever is deeper, and the excess liner material is to be disposed of at an authorized disposal site.
- Corner two will be rounded to keep the fill on the ledge west of the site.
- The reserve pit will be lined with a double layer of felt and a 20 mil liner.

COAs: Page 3 of 7 Well: NBU 649-26E

DOWNHOLE PROGRAM CONDITIONS OF APPROVAL (COAs)

SITE SPECIFIC DOWNHOLE COAs:

 Production casing cement shall be brought up and into the surface casing. The minimum cement top is 200 ft above the surface casing shoe.
 COA specification is consistent with operators performance standard stated in APD.

- A variance is granted for Onshore Order #2 Drilling Operations III. E. "Blooie line discharge 100 feet from well bore and securely anchored" Blooie line can be 75 feet.

 All requirements will be adhered to covering air/gas drilling operations as described in Onshore Order #2 III. E. 1. Drilling Operations, Special Drilling Operations, air/gas drilling.
- Covering air/gas drilling operations, requirements will be adhered to covering air/gas drilling operations as described in Onshore Order #2 III. E. 1. Drilling Operations, Special Drilling Operations, air/gas drilling.
- A Gamma Ray well Log shall be run from the well Total Depth to the surface. A copy of the Gamma Ray well Log shall be submitted to the BLM Vernal Field Office.

All provisions outlined in Onshore Oil & Gas Order #2 Drilling Operations shall be strictly adhered to. The following items are emphasized:

DRILLING/COMPLETION/PRODUCING OPERATING STANDARDS

- The spud date and time shall be reported orally to Vernal Field Office within 24 hours of spudding.
- Notify Vernal Field Office Supervisory Petroleum Engineering Technician at least 24 hours in advance of casing cementing operations and BOPE & casing pressure tests.
- Blowout prevention equipment (BOPE) shall remain in use until the well is completed or abandoned. Closing unit controls shall remain unobstructed and readily accessible at all times. Choke manifolds shall be located outside of the rig substructure.
- All BOPE components shall be inspected daily and those inspections shall be recorded in the daily drilling report. Components shall be operated and tested as required by Onshore Oil & Gas Order No. 2 to insure good mechanical working order. All BOPE pressure tests shall be performed by a test pump with a chart recorder and **NOT** by the rig pumps. Test shall be reported in the driller's log.
- BOP drills shall be initially conducted by each drilling crew within 24 hours of drilling out from under the surface casing and weekly thereafter as specified in Onshore Oil & Gas Order No. 2.

COAs: Page 4 of 7 Well: NBU 649-26E

• Casing pressure tests are required before drilling out from under all casing strings set and cemented in place.

- No aggressive/fresh hard-banded drill pipe shall be used within casing.
- Cement baskets shall not be run on surface casing.
- The operator must report all shows of water or water-bearing sands to the BLM. If flowing water is encountered it must be sampled, analyzed, and a copy of the analyses submitted to the BLM Vernal Field Office.
- The operator must report encounters of all non oil & gas mineral resources (such as Gilsonite, tar sands, oil shale, trona, etc.) to the Vernal Field Office, in writing, within 5 working days of each encounter. Each report shall include the well name/number, well location, date and depth (from KB or GL) of encounter, vertical footage of the encounter and, the name of the person making the report (along with a telephone number) should the BLM need to obtain additional information.
- A complete set of angular deviation and directional surveys of a directional well will be submitted to the Vernal BLM office engineer within 30 days of the completion of the well.
- While actively drilling, chronologic drilling progress reports shall be filed directly with the BLM, Vernal Field Office on a weekly basis in sundry, letter format or e-mail to the Petroleum Engineers until the well is completed.
- A cement bond log (CBL) will be run from the production casing shoe to the <u>top of cement</u> and shall be utilized to determine the bond quality for the production casing. Submit a field copy of the CBL to this office.
- Please submit an electronic copy of all other logs run on this well in LAS format to UT_VN_Welllogs@BLM.gov. This submission will supersede the requirement for submittal of paper logs to the BLM.
- There shall be no deviation from the proposed drilling, completion, and/or workover program as approved. Safe drilling and operating practices must be observed. Any changes in operation must have prior approval from the BLM Vernal Field Office.

COAs: Page 5 of 7 Well: NBU 649-26E

OPERATING REQUIREMENT REMINDERS:

• All wells, whether drilling, producing, suspended, or abandoned, shall be identified in accordance with 43 CFR 3162.6. There shall be a sign or marker with the name of the operator, lease serial number, well number, and surveyed description of the well.

- In accordance with 43 CFR 3162.4-3, this well shall be reported on the "Monthly Report of Operations" (Oil and Gas Operations Report ((OGOR)) starting with the month in which operations commence and continue each month until the well is physically plugged and abandoned. This report shall be filed in duplicate, directly with the Minerals Management Service, P.O. Box 17110, Denver, Colorado 80217-0110, or call 1-800-525-7922 (303) 231-3650 for reporting information.
- Should the well be successfully completed for production, the BLM Vernal Field office must be notified when it is placed in a producing status. Such notification will be by written communication and must be received in this office by not later than the fifth business day following the date on which the well is placed on production. The notification shall provide, as a minimum, the following informational items:
 - Operator name, address, and telephone number.
 - Well name and number.
 - o Well location (1/41/4, Sec., Twn, Rng, and P.M.).
 - O Date well was placed in a producing status (date of first production for which royalty will be paid).
 - The nature of the well's production, (i.e., crude oil, or crude oil and casing head gas, or natural gas and entrained liquid hydrocarbons).
 - o The Federal or Indian lease prefix and number on which the well is located; otherwise the non-Federal or non-Indian land category, i.e., State or private.
 - o Unit agreement and/or participating area name and number, if applicable.
 - o Communitization agreement number, if applicable.
- Any venting or flaring of gas shall be done in accordance with Notice to Lessees (NTL) 4A and needs prior approval from the BLM Vernal Field Office.
- All undesirable events (fires, accidents, blowouts, spills, discharges) as specified in NTL 3A will be reported to the BLM, Vernal Field Office. Major events, as defined in NTL3A, shall be reported verbally within 24 hours, followed by a written report within 15 days. "Other than Major Events" will be reported in writing within 15 days. "Minor Events" will be reported on the Monthly Report of Operations and Production.

COAs: Page 6 of 7 Well: NBU 649-26E

• Whether the well is completed as a dry hole or as a producer, "Well Completion and Recompletion Report and Log" (BLM Form 3160-4) shall be submitted not later than 30 days after completion of the well or after completion of operations being performed, in accordance with 43 CFR 3162.4-1. Two copies of all logs run, core descriptions, and all other surveys or data obtained and compiled during the drilling, workover, and/or completion operations, shall be filed on BLM Form 3160-4. Submit with the well completion report a geologic report including, at a minimum, formation tops, and a summary and conclusions. Also include deviation surveys, sample descriptions, strip logs, core data, drill stem test data, and results of production tests if performed. Samples (cuttings, fluid, and/or gas) shall be submitted only when requested by the BLM, Vernal Field Office.

- All off-lease storage, off-lease measurement, or commingling on-lease or off-lease, shall have prior written approval from the BLM Vernal Field Office.
- Oil and gas meters shall be calibrated in place prior to any deliveries. The BLM Vernal Field Office Petroleum Engineers will be provided with a date and time for the initial meter calibration and all future meter proving schedules. A copy of the meter calibration reports shall be submitted to the BLM Vernal Field Office. All measurement facilities will conform to the API standards for liquid hydrocarbons and the AGA standards for natural gas measurement. All measurement points shall be identified as the point of sale or allocation for royalty purposes.
- A schematic facilities diagram as required by Onshore Oil & Gas Order No. 3 shall be submitted to the BLM Vernal Field Office within 30 days of installation or first production, whichever occurs first. All site security regulations as specified in Onshore Oil & Gas Order No. 3 shall be adhered to. All product lines entering and leaving hydrocarbon storage tanks will be effectively sealed in accordance with Onshore Oil & Gas Order No. 3.
- Any additional construction, reconstruction, or alterations of facilities, including roads, gathering lines, batteries, etc., which will result in the disturbance of new ground, shall require the filing of a suitable plan and need prior approval of the BLM Vernal Field Office. Emergency approval may be obtained orally, but such approval does not waive the written report requirement.
- No location shall be constructed or moved, no well shall be plugged, and no drilling or workover
 equipment shall be removed from a well to be placed in a suspended status without prior
 approval of the BLM Vernal Field Office. If operations are to be suspended for more than 30
 days, prior approval of the BLM Vernal Field Office shall be obtained and notification given
 before resumption of operations.
- Pursuant to Onshore Oil & Gas Order No. 7, this is authorization for pit disposal of water produced from this well for a period of 90 days from the date of initial production. A permanent disposal method must be approved by this office and in operation prior to the end of this 90-day period. In order to meet this deadline, an application for the proposed permanent disposal method shall be submitted along with any necessary water analyses, as soon as possible, but no later than 45 days after the date of first production. Any method of disposal which has not been approved prior to the end of the authorized 90-day period will be considered as an Incident of Noncompliance and will be grounds for issuing a shut-in order until an acceptable manner for disposing of said water is provided and approved by this office.

COAs: Page 7 of 7 Well: NBU 649-26E

• Unless the plugging is to take place immediately upon receipt of oral approval, the Field Office Petroleum Engineers must be notified at least 24 hours in advance of the plugging of the well, in order that a representative may witness plugging operations. If a well is suspended or abandoned, all pits must be fenced immediately until they are backfilled. The "Subsequent Report of Abandonment" (Form BLM 3160-5) must be submitted within 30 days after the actual plugging of the well bore, showing location of plugs, amount of cement in each, and amount of casing left in hole, and the current status of the surface restoration.

10

Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVE	ΞĽ
OMB NO. 1004-01	3
Expires: July 31, 20	1

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

abandoned well. Hea form 2160-2 (APD) for such proposals

5,	Lease Serial No. UTU472	

abandoned well. Use form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or	Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side.				7. If Unit or CA/Agreement, Name and/or No. NATURAL BUTTES		
1. Type of Well ☐ Oil Well ☐ Gas Well ☐ Other				8. Well Name and No. NATURAL BUTTES UNIT 649-26E		
Name of Operator EOG RESOURCES, INC.		IICKENZIE THACKER®		ES.COM	9. API Well No. 43-047-39870	
3a. Address 1060 E. HWY 40 VERNAL, UT 84078		3b. Phone No Ph: 435-78	. (include area code) 1-9145)	10. Field and Pool, or Exploratory NATURAL BUTTES	
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description)				11. County or Parish, and State	
Sec 26 T10S R22E NWNE 66 39.92527 N Lat, 109.40398 W					UINTAH COUNTY, UT	
12. CHECK APPE	ROPRIATE BOX(ES) TO I	INDICATE	NATURE OF 1	NOTICE, RI	EPORT, OR OTHEF	RDATA
TYPE OF SUBMISSION			TYPE O	F ACTION		
➤ Notice of Intent	☐ Acidize	☐ Dee	pen	☐ Product	ion (Start/Resume)	☐ Water Shut-Off
_	☐ Alter Casing	☐ Frac	ture Treat	□ Reclam	ation	■ Well Integrity
☐ Subsequent Report	□ Casing Repair	□ New	Construction	☐ Recomp	olete	Other
☐ Final Abandonment Notice	☐ Change Plans	Plug	and Abandon	□ Tempor	arily Abandon	Change to Original A PD
	☐ Convert to Injection	Plug	Back	□ Water I	Disposal	
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) EOG Resources, Inc. respectfully requests to change the TD for the referenced well from Approved by the Utah Division of to Oil, Gas and Mining 7052'. COPY SENT TO OPERATOR Date: 1-27-299 Initials:						
14. I hereby certify that the foregoing is true and correct. Electronic Submission #66426 verified by the BLM Well Information System For EOG RESOURCES, INC., sent to the Vernal						
Name (Printed/Typed) MICKENZ	IE THACKER		Title OPERA	TIONS CLE	RK	
Signature Willermopia Submit Apacher Date 01/19/2009						
THIS SRACE FOR FEDERAL OR STATE OFFICE USE						
Approved By Conditions of approval, if any, are attached entify that the applicant holds legal or equivalent would entitle the applicant to conductive the applicant to c	nitable title to those rights in the su		Title Office			Date
	itle 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.					

** OPERATOR-SUBMITTED ** OPERATOR-SUBMITTED **

JAN 2 1 2009

	STATE OF UTAH		FORM 9
	5.LEASE DESIGNATION AND SERIAL NUMBER: UTU472		
SUNDF	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:		
	sals to drill new wells, significantly deepen igged wells, or to drill horizontal laterals. I		7.UNIT or CA AGREEMENT NAME: NATURAL BUTTES
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: NBU 649-26E
2. NAME OF OPERATOR: EOG Resources, Inc.			9. API NUMBER: 43047398700000
3. ADDRESS OF OPERATOR: 1060 East Highway 40 , Verna	al, UT, 84078 435 781-91	PHONE NUMBER: 111 Ext	9. FIELD and POOL or WILDCAT: NATURAL BUTTES
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0661 FNL 1759 FEL			COUNTY: UINTAH
QTR/QTR, SECTION, TOWNSHI Qtr/Qtr: NWNE Section: 26	IP, RANGE, MERIDIAN: Township: 10.0S Range: 22.0E Meridian:	S	STATE: UTAH
11. CHE	CK APPROPRIATE BOXES TO INDICA	TE NATURE OF NOTICE, REPORT,	OR OTHER DATA
TYPE OF SUBMISSION		TYPE OF ACTION	
	CHANGE TO PREVIOUS PLANS CHANGE WELL STATUS DEEPEN OPERATOR CHANGE PRODUCTION START OR RESUME REPERFORATE CURRENT FORMATION TUBING REPAIR WATER SHUTOFF WILDCAT WELL DETERMINATION OMPLETED OPERATIONS. Clearly show all per respectfully requests the APD extended for one year.	for the referenced well be	
NAME (PLEASE PRINT) Mickenzie Gates	PHONE NUMBER 435 781-9145	TITLE Operations Clerk	
SIGNATURE N/A	433 /81-9145	DATE 11/20/2009	



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43047398700000

API: 43047398700000 Well Name: NBU 649-26E

Location: 0661 FNL 1759 FEL QTR NWNE SEC 26 TWNP 100S RNG 220E MER S

Company Permit Issued to: EOG RESOURCES, INC.

Date Original Permit Issued: 12/17/2007

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not

uire revi	sion. Following is a cl	necklist of som	e items related to tl	ne applicatio	n, which should be verified.
	ated on private land, l ed? 🗍 Yes 📵 No	has the owners	ship changed, if so,	has the surfa	ice agreement been
	any wells been drilled requirements for this			ell which wou	uld affect the spacing or
	nere been any unit or s proposed well?		ents put in place tha	t could affec	t the permitting or operatio
	there been any chang the proposed locatio			wnership, or	rightof- way, which could
• Has th	ne approved source o	f water for dril	ling changed? 🗍	Yes 📵 No	
	there been any physi e in plans from what				oute which will require a Yes 📵 No
• Is bor	nding still in place, wl	nich covers thi	s proposed well? 🬘	Yes 🗍 I	Approved by the No Utah Division of Oil, Gas and Mining
nature:	Mickenzie Gates	Date: 11/2	20/2009		
Title:	Operations Clerk Repr	esentina: EOG	RESOURCES, INC.	Dat	te: November 23, 2009
	- p				100000

Sig

By: Dolly

	FORM 9			
	5.LEASE DESIGNATION AND SERIAL NUMBER: UTU472			
SUNDF	6. IF INDIAN, ALLOTTEE OR TRIBE NAME:			
	sals to drill new wells, significantly deepen igged wells, or to drill horizontal laterals. U		7.UNIT or CA AGREEMENT NAME: NATURAL BUTTES	
1. TYPE OF WELL Gas Well			8. WELL NAME and NUMBER: NBU 649-26E	
2. NAME OF OPERATOR: KERR-MCGEE OIL & GAS ONS	HORE, L.P.		9. API NUMBER: 43047398700000	
3. ADDRESS OF OPERATOR: P.O. Box 173779 1099 18th S	PHOI treet, Suite 600, Denver, CO, 80217 3779	NE NUMBER: 720 929-6007 Ext	9. FIELD and POOL or WILDCAT: NATURAL BUTTES	
4. LOCATION OF WELL FOOTAGES AT SURFACE: 0661 FNL 1759 FEL			COUNTY: UINTAH	
QTR/QTR, SECTION, TOWNSHI	P, RANGE, MERIDIAN: Township: 10.0S Range: 22.0E Meridian:	S	STATE: UTAH	
11. CHE	CK APPROPRIATE BOXES TO INDICAT	E NATURE OF NOTICE, REPORT,	OR OTHER DATA	
TYPE OF SUBMISSION		TYPE OF ACTION		
✓ NOTICE OF INTENT	ACIDIZE	☐ ALTER CASING	CASING REPAIR	
Approximate date work will start: 12/14/2010	☐ CHANGE TO PREVIOUS PLANS ☐ CHANGE WELL STATUS	☐ CHANGE TUBING ☐ COMMINGLE PRODUCING FORMATIONS	☐ CHANGE WELL NAME ☐ CONVERT WELL TYPE	
SUBSEQUENT REPORT Date of Work Completion:	DEEPEN	FRACTURE TREAT	□ NEW CONSTRUCTION	
	☐ PRODUCTION START OR RESUME	☐ PLUG AND ABANDON ☐ RECLAMATION OF WELL SITE	☐ PLUG BACK☐ RECOMPLETE DIFFERENT FORMATION	
SPUD REPORT Date of Spud:	REPERFORATE CURRENT FORMATION	SIDETRACK TO REPAIR WELL	☐ TEMPORARY ABANDON	
DRILLING REPORT	☐ TUBING REPAIR ☐ WATER SHUTOFF	U VENT OR FLARE☐ SI TA STATUS EXTENSION		
Report Date:	☐ WILDCAT WELL DETERMINATION	OTHER	OTHER:	
Kerr-McGee Oil & G extension to this A	as Onshore, L.P. (Kerr-McGee as Onshore, L.P. (Kerr-McGee APD for the maximum time allowith any questions and/or con) respectfully requests an owed. Please contact the nments. Thank you.	Approved by the Utah Division of Oil, Gas and Mining ate: 12/23/2010 y:	
NAME (PLEASE PRINT) Danielle Piernot	PHONE NUMBER 720 929-6156	TITLE Regulatory Analyst		
SIGNATURE N/A		DATE 12/14/2010		



The Utah Division of Oil, Gas, and Mining

- State of Utah
- Department of Natural Resources

Electronic Permitting System - Sundry Notices

Request for Permit Extension Validation Well Number 43047398700000

API: 43047398700000 **Well Name:** NBU 649-26E

Location: 0661 FNL 1759 FEL QTR NWNE SEC 26 TWNP 100S RNG 220E MER S

Company Permit Issued to: KERR-MCGEE OIL & GAS ONSHORE, L.P.

Date Original Permit Issued: 12/17/2007

The undersigned as owner with legal rights to drill on the property as permitted above, hereby verifies that the information as submitted in the previously approved application to drill, remains valid and does not require revision. Following is a checklist of some items related to the application, which should be verified.

require revi	sion. Following is a chec	klist of some it	ems related to the	e application	, which should be verified.
	ated on private land, has ed?	the ownership	changed, if so, h	as the surfac	e agreement been
	any wells been drilled in requirements for this lo			l which woul	d affect the spacing or
	nere been any unit or ot s proposed well?		s put in place that	could affect	the permitting or operation
	there been any changes the proposed location?		oute including ow No	nership, or r	ightof- way, which could
• Has tl	ne approved source of w	ater for drilling	g changed? 🔵 Y	es 📵 No	
	there been any physical e in plans from what wa				ite which will require a es No
• Is bor	nding still in place, which	h covers this pi	oposed well? 🌘		Approved by the Outah Division of Oil, Gas and Mining
Signature:	Danielle Piernot	Date: 12/14	1/2010 MCCEE OIL 8: CAS	ONCHORD ##	12/23/2010
ı itie:	Regulatory Analyst Repre	esenting: KERR	-MCGEE OIL & GAS	UNSHUKE PL.	£ 00.01/10



State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER
Executive Director

Division of Oil, Gas and Mining

JOHN R. BAZA

Division Director

January 5, 2012

Danielle Piernot Kerr-McGee Oil & Gas Onshore, L.P. P.O. Box 173779 Denver, CO 80217

Re:

APD Rescinded - NBU 649-26E, Sec. 26, T.10S, R. 22E

Uintah County, Utah API No. 43-047-39870

Ladies and Gentlemen:

The Application for Permit to Drill (APD) for the subject well was approved by the Division of Oil, Gas and Mining (Division) on December 17, 2007. On December 1, 2008, November 23, 2009 and December 23, 2010 the Division granted a one-year APD extension. On January 5, 2012, you requested that the division rescind the state approved APD. No drilling activity at this location has been reported to the division. Therefore, approval to drill the well is hereby rescinded, effective January 5, 2012.

If any previously unreported operations have been performed on this well location, it is imperative that you notify the Division immediately.

Sincerely,

Diana Mason

Environmental Scientist

cc:

Well File

Bureau of Land Management, Vernal





United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Green River District Vernal Field Office 170 South 500 East Vernal, UT 84078

http://www.blm.gov/ut/st/en/fo/vernal.html

JUN 2 6 2012

IN REPLY REFER TO: 3160 (UTG011)

Julie Jacobson Anadarko Petroleum Corporation Kerr McGee Oil & Gas Onshore LP 1099 18th Street, Suite 600 Denver, CO 80202

Re:

Notice of Expiration Well No. NBU 649-26E NWNE, Sec. 26, T10S, R22E Uintah County, Utah Lease No. UTU-472 Natural Buttes Unit

Dear Ms. Jacobson:

The Application for Permit to Drill (APD) for the above-referenced well was approved on December 24, 2008. No extension request of the original APD was received. According to our records, no known activity has transpired at the approved location. In view of the foregoing, this office is notifying you that the approval of the referenced application has expired. If you intend to drill at this location in the future, a new Application for Permit to Drill must be submitted.

This office requires a letter confirming that no surface disturbance has been made for this drill site. Any surface disturbance associated with the approved location of this well is to be rehabilitated. A schedule for this rehabilitation must be submitted to this office. Your cooperation in this matter is appreciated.

If you have any questions regarding this matter, please contact Cindy Severson at (435) 781-4455.

Sincerely,

Jerry Kenczka

Assistant Field Manager Lands & Mineral Resources

43 047 39870

CC:

UDOGM

RECEIVED

JUL 0 3 2012